

E-WALL SERIES

Outdoor Customized Cabinet

E-wall

| | |
|--------------|--------------------------------------|
| Models | : EW2,EW3,EW4,EW4.8,EW5,EW6,EW8,EW10 |
| Pixels | : P2.5,P3, P4,P4.8, P5, P6, P8, P10 |
| Cabinet Size | : CUSTOMISABLE |
| LED Type | : SMD |
| Material | : GI |
| Weight | : 14Kg SQM |
| Warranty | : 2 years |



Easy Maintenance



Slim Thickness



Weight Less



High Brightness



Features

- › Outdoor prime series module
- › PWM driver IC, 4K refresh rate, no waterless ripple.
- › The kit is made of high-grade raw materials, with good toughness and not easy to be deformed.
- › LED lamp is well split and have good brightness uniformity.
- › Mechanical engineering design of reinforcing ribs to ensure product flatness..

Specifications

| | |
|--|---------------------------------|
| Items | EW4 |
| Scanning Mode | 1/8 |
| Pixel Pitch | 4 |
| Module Resolution | 80*40 |
| Module Size (CM) | 32*16 |
| Pixel Density | 27777 |
| Brightness (cd/m ²) | >5500 |
| Module Weight (Kg) | 0.35 |
| Max Current (A) | <7.75 |
| Screen Power Consumption (W/M ²) | <946 |
| Optimum Viewing Distance (m) | > 6 |
| LED Encapsulation | SMD2525 |
| Driving IC | PWM-SS IC |
| Refresh Rate(Hz) | >3840 |
| Optimum Viewi Angle (°) | Horizontal:140° Vertical : 130° |
| Gray Scale(Bit) | 14-16 |
| Attenuation | <15% |
| MTBF | > 10000hours |
| Defective Rate | <0.0003, 0 before delivery |
| IP Grade | IP65 (Front side) |

Applications



- Advertisements
- Signage Display

- Smart City Projects
- Posters

- Traffic Signs
- Public Informations

- Road Medians
- Stadium Screens